INTERNOVA
PROFESSIONAL LIGHTING

PRODUCT DATASHEET




CUBO • BLACK

# CUBO
## SURFACE MOUNTED LIGHTING

made in HOLLAND

### AVAILABLE IN







| | |
|---|---|
| **Lumen output** | 2x 160lm |
| **CRI** | >80Ra |
| **CCT** | 2300K • 2700K • 3000K |

## FIXTURE SPECIFICATIONS

View product on website




**Fixture weight:** 720 grams

| | |
|---|---|
| **Housing material** | Die cast aluminium |
| **Material finish** | Powder coating |
| **RAL colour** | 9004 (Black) • 9003 (White) |
| **Fixture type** | Wall mounted Light |
| **LED Module** | CREE LED's |
| **Driver** | Osram Triac dimmable driver |
| **Number of light sources** | 2 |
| **Adjustability** | Fixed |
| **IP rating** | IP65 |
| **Expected lifetime** | L70 / B50 @ 50.000 hours |
| **Photobiological safety** | RG1 Unlimited |
| **UGR** | < 19 |
| **Power factor** | > 0.9 |
| **Colour consistency** | 3 SDCM |
| **Warranty** | 5 years on LED module and driver |


© 2025 INTERNOVA PROFESSIONAL LIGHTING BV

INTERNOVA
PROFESSIONAL LIGHTING

## **FIXTURE** VARIATIONS

| LED module | Lumen | Light colour | Efficiency (Lm/W) | Power | Dim options |
|---|---|---|---|---|---|
| Citizen LED | 2x 160lm | 923 / 927 / 930 | 53 | 6W | Triac |

Fixture variations:
[1]) Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)
[2]) Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerence of up to +/- 150 Kelvin compared to nominal value.
[3]) Fixture efficiency is displayed in lumens per watt and is calculated based on the net lumen output and power consumption of both the LED module and driver.
[4]) Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting BV without prior notice.

## **ARTICLE CODE** CONFIGURATOR

IN

Clear filters

**LIGHT COLOUR**

- 2300K
- 2700K
- 3000K

**FIXTURE COLOUR**

Article code configurator:
[1]) This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome

Rithmeesterpark 21 | 4838 GZ Breda | The Netherlands
+31 (0) 76 520 5566 | info@internova.nl


© 2025 INTERNOVA PROFESSIONAL LIGHTING BV