



## PIEGA

### 48V TRACK LIGHTING

#### AVAILABLE IN




| Reflector                                                                         |                                                                                   | Led module                                                                        | Dim options                                                                         |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reflector                                                                         | Reflector                                                                         | Standard                                                                          | Dimmable                                                                            |
|  |  |  |  |

|              |               |
|--------------|---------------|
| Lumen output | 450lm         |
| CRI          | >90Ra         |
| CCT          | 2700K • 3000K |

made in  
**HOLLAND**

## FIXTURE SPECIFICATIONS

 [View product on website](#)



Fixture weight: 162 grams



|                         |                                  |
|-------------------------|----------------------------------|
| Housing material        | Die cast aluminium               |
| Material finish         | Matte coating                    |
| RAL colour              | 9004 (Black) • 9003 (White)      |
| Fixture type            | 48V low voltage track light      |
| LED Module              | Bridgelux SMD 2835               |
| Driver                  | Powergear 48V in-track adapter   |
| Number of light sources | 6                                |
| Adjustability           | 350° rotatable and 90° tiltable  |
| IP rating               | IP20                             |
| Expected lifetime       | L90 / B10 @ 100.000 hours        |
| Photobiological safety  | RG1 Unlimited                    |
| Power factor            | > 0.9                            |
| Colour consistency      | 3 SDCM                           |
| Warranty                | 5 years on LED module and driver |

## FIXTURE VARIATIONS

| LED module         | Lumen | Light colour | Efficiency (Lm/W) | Power | Dim options |
|--------------------|-------|--------------|-------------------|-------|-------------|
| Bridgelux SMD 2835 | 450lm | 927 / 930    | 75                | 6.0W  | DALI        |

Fixture variations:

- <sup>1)</sup> Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)
- <sup>2)</sup> Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerance of up to +/- 150 Kelvin compared to nominal value.
- <sup>3)</sup> Fixture efficiency is displayed in lumens per watt and is calculated based on the gross lumen output and power consumption of both the LED module and driver
- <sup>4)</sup> Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting without prior notice.

## ARTICLE CODE CONFIGURATOR

IN

Clear filters

**LUMEN OUTPUT**

☒ 450lm

**LIGHT COLOUR**

☐ 2700K
 ☐ 3000K

**REFLECTOR**

☐ 24°
 ☐ 40°

**FIXTURE COLOUR**

☐ Black
 ☐ Black / Gold
 ☐ Black / White
 ☐ White
 ☐ White / Gold
 ☐ White / Black

**DIM OPTIONS**

☐ On/off
 ☒ DALI dim

Article code configurator:

- <sup>1)</sup> This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome