



## SOTTILE 40

### 48V TRACK LIGHTING

made in  
**HOLLAND**

#### AVAILABLE IN




| Reflector                                                                         |                                                                                   |                                                                                   | Led module                                                                         | Dim options                                                                         |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Reflector                                                                         | Reflector                                                                         | Reflector                                                                         | Standard                                                                           | Dimmable                                                                            |
|  |  |  |  |  |

|              |               |
|--------------|---------------|
| Lumen output | 900lm         |
| CRI          | >90Ra         |
| CCT          | 2700K • 3000K |

## FIXTURE SPECIFICATIONS

 [View product on website](#)



Fixture weight: 162 grams



|                         |                                           |
|-------------------------|-------------------------------------------|
| Housing material        | Die cast aluminium                        |
| Material finish         | Powder coating                            |
| RAL colour              | 9005 (Black) • 9016 (White) • 1036 (Gold) |
| Fixture type            | 48V low voltage track light               |
| LED Module              | Bridgelux V6 HD LED                       |
| Driver                  | Powergear 48V in-track adapter            |
| Number of light sources | 1                                         |
| Adjustability           | 350° rotatable and 90° tiltable           |
| IP rating               | IP20                                      |
| Expected lifetime       | L90 / B10 @ 70.000 hours                  |
| Photobiological safety  | RG1 Unlimited                             |
| Power factor            | > 0.9                                     |
| Colour consistency      | 3 SDCM                                    |
| Warranty                | 3 years on LED module and driver          |

## FIXTURE VARIATIONS

| LED module          | Lumen | Light colour | Efficiency (Lm/W) | Power  | Dim options |
|---------------------|-------|--------------|-------------------|--------|-------------|
| Bridgelux V6 HD LED | 900lm | 927          | 75                | 12.0 W | DALI        |
| Bridgelux V6 HD LED | 900lm | 930          | 75                | 12.0 W | DALI        |

Fixture variations:

- <sup>1)</sup> Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)
- <sup>2)</sup> Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerance of up to +/- 150 Kelvin compared to nominal value.
- <sup>3)</sup> Fixture efficiency is displayed in lumens per watt and is calculated based on the gross lumen output and power consumption of both the LED module and driver
- <sup>4)</sup> Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting without prior notice.

## ARTICLE CODE CONFIGURATOR

IN

Clear filters

### LUMEN OUTPUT

☒ 900lm

### LIGHT COLOUR

☐ 2700K

☐ 3000K

### REFLECTOR

☐ 15° ☐ 40°

☐ 24°

### FIXTURE COLOUR

☐ Black

☐ Black / Gold

☐ Black / White

☐ White

☐ White / Gold

☐ White / Black

### DIM OPTIONS

☐ On/off

☐ DALI dim

Article code configurator:

- <sup>1)</sup> This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome

POLAR

DIAGRAMS

